



Are luminescent bacteria suitable for online detection and monitoring of toxic compounds in drinking water and its sources?

BTO 2011.011
January 2011

Are luminescent bacteria suitable for online detection and monitoring of toxic compounds in drinking water and its sources?

BTO 2011.011
January 2011

© 2011 KWR

All rights reserved. No part of this book may be reproduced, stored in a database or retrieval system, or published, in any form or in any way, electronically, mechanically, by print, photoprint, microfilm or any other means without prior written permission from the publisher.

Colofon

Title

Are luminescent bacteria suitable for online detection and monitoring of toxic compounds in drinking water and its sources?

Project number

B111658

Onderzoeksprogramma('s)

Chemical Waterquality and Health

Project manager

Merijn Schriks

Client

BTO

Quality Assurance

Annemarie P. van Wezel

Author(s)

Marjolijn Woutersen, Shimshon Belkin, Bram Brouwer, Annemarie P. van Wezel and Minne Heringa

Sent to

This report has been distributed among BTO-participants and is publicly available.

Preface

Biosensors based on luminescent bacteria may be valuable tools to monitor the chemical quality and safety of surface and drinking water. In this review, an overview is presented of the recombinant strains available that harbour the bacterial luciferase genes *luxCDABE*, and which may be used in an online biosensor for water quality monitoring. Many bacterial strains have been described for the detection of a broad range of toxicity parameters, including DNA damage, protein damage, membrane damage, oxidative stress, organic pollutants, and heavy metals. Most lux strains have sensitivities with detection limits ranging from milligrams per litre to micrograms per litre, usually with higher sensitivities in compound-specific strains. Although the sensitivity of lux strains can be enhanced by various molecular manipulations, most reported detection thresholds are still too high to detect levels of individual contaminants as they occur nowadays in European drinking waters. However, lux strains sensing specific toxic effects have the advantage of being able to respond to mixtures of contaminants inducing the same effect, and thus could be used as a sensor for the sum effect, including the effect of compounds that are as yet not identified by chemical analysis. An evaluation of the suitability of lux strains for monitoring surface and drinking water is therefore provided.

Samenvatting

Zijn luminescente bacteriën geschikt voor het detecteren en monitoren van giftige stoffen in drinkwater en drinkwaterbronnen?

Sensoren gebaseerd op luminescente bacteriën zijn mogelijk waardevolle hulpmiddelen bij het monitoren van de chemische waterkwaliteit en veiligheid van oppervlakte en drinkwater. In deze review wordt een overzicht gegeven van de beschikbare recombinante stammen, welke de bacteriële luciferase genen *luxCDABE* hebben en mogelijk gebruikt kunnen worden in een sensor voor de continue monitoring van de chemische waterkwaliteit. Een groot aantal bacterie stammen is beschreven voor een brede range aan toxicologische parameters, zoals schade aan DNA, eiwitten of membranen, oxidatieve stress, organische verontreinigingen en zware metalen. De meeste van deze lux stammen hebben een gevoeligheid in de milligram tot microgram per liter range, waarbij de stof specifieke stammen doorgaans gevoeliger zijn. Hoewel er verschillende moleculaire manipulaties zijn waarmee de gevoeligheid van lux stammen verhoogd kan worden, zijn de meeste detectie grenzen nog te hoog om individuele stoffen aan te tonen in Europees drinkwater. De lux stammen die op effecten reageren, kunnen echter wel gebruikt worden om het som effect te meten van een mix van stoffen. Hiermee worden dan ook stoffen gedetecteerd die niet worden bepaald bij routinematige chemische analyses. In de discussie wordt een evaluatie gemaakt van de verschillende lux stammen en hun geschiktheid voor oppervlakte en drinkwater monitoring.

Contents

1	Introduction	7
2	Effect-specific <i>lux</i> strains	9
3	Compound specific strains	15
4	Discussion	19
5	Conclusion	23
6	Acknowledgments	25
7	References	27

1 Introduction


To ensure the chemical quality and safety of drinking water, it is essential to monitor the surface water sources as well as critical points in the distribution network. Currently, the presence of toxic chemicals in water is investigated by chemical analysis, by using aquatic organisms as biomonitors, and by *in vitro* toxicity assays [1]. Chemical analysis is quantitative, sensitive, and highly selective, but only target compounds are detected. The biomonitoring methods, using mussels, *Daphnia*, algae, or natural bacteria are able to detect the total, mostly systemic, acute toxic effects of compounds such as herbicides and heavy metals. However, the toxic effects in these organisms have little predictive value for possible hazards for human individuals. In addition, these biomonitors do not react to non-systemic, specific toxic effects of compounds such as genotoxicants and endocrine disruptors. *In vitro* toxicity assays, using human or other mammalian cell lines, provide information on hazards relevant for human toxicity and can detect the sum effect of the whole mixture of toxicants present. For real-time monitoring of toxicants in water, there is currently no suitable system available that provides relevant information about human hazards. This gap may be filled by a type of biosensor that employs genetically modified luminescent bacteria which provide a rapid, easily measurable response in the presence of relevant toxic (mixtures of) compounds. A rapidly growing number of luminescent bacteria have already been constructed and described, which may be applicable for toxicity detection in water.

In this paper, an overview is provided of available bacterial *luxCDABE* strains and an evaluation and concurrent selection of strains which might be used in a biosensor for water quality monitoring. Lowe defined a biosensor as "an analytical device, which converts the concentration of the target substance into an electrical signal through a combination of a biological recognition system associated with a physico-chemical transducer" [2]. For a toxic compound to elicit a measurable response in bacterial cells in a biosensor, it first has to cross the cell wall and cell membrane. Then, it has to trigger a sensing element, in most cases a promoter linked to a reporter gene, leading to the production of easily measurable reporter proteins. Detailed reviews have been written by van der Meer *et al.* which explain the mechanisms involved in the cellular transport and activation mechanisms of analytes [3,4].

Currently, the most commonly used reporter proteins for optical detection in microbial systems are GFP for fluorescence and bacterial luciferase for luminescence. Bioluminescence offers the advantages of faster response times and higher short-term sensitivity (seconds to minutes). Fluorescent proteins may keep accumulating for many hours and due to their high stability, allow detection even after cell death [5-7]. GFP also does not require substrate or ATP, thereby lowering the burden on the cells [3]. For on-line monitoring of water, sensitivity and fast response times are more important factors than reporter stability. Therefore, luminescence is the detection method of choice for on-line monitoring, and this overview will thus focus on available luminescent bacterial reporter strains.

Bioluminescent bacteria express luminescence through the production of luciferase, either bacterial (*lux*) or firefly (*luc*). The latter has the advantage of a higher quantum yield, but requires the constant addition of luciferine. As a result, bacterial luciferase is favoured in most cases [8].

Bacterial luciferase catalyses the oxidation of a long-chain aliphatic aldehyde (R-CHO and a reduced flavin mononucleotide (FMNH₂). In this reaction, free energy is emitted in the form of light with a wavelength of 490 nm:



As this reaction depends on a functional electron transport system, it only functions in viable cells [9]. Of the bacterial luciferase operon, only the *luxAB* genes are required for luminescence; however in this case a substrate has to be administered externally. More practical for on-line monitoring is the use of the *luxCDABE* genes, in which *luxCDE* code for the (re)generation of the substrate [10]. Thus, no substrate addition is necessary and the luciferase reporter can operate independently. This overview will thus be limited to strains with the five bacterial luciferase genes, *luxCDABE* (*lux* strains).

Assays using bioluminescent bacteria can be divided into two groups, namely systems with constitutive and systems with inducible expression. Bacteria with constitutive expression have normally a high expression of luminescence, which decreases under toxic conditions ('lights off'). They are usually natural bioluminescent bacteria, such as *Aliivibrio fischeri* (until recently known as *Vibrio fischeri*), and are often used to detect acute (cyto)toxicity, as the response is not compound-specific. The use of these bacteria is categorized under biomonitors, as it involves natural aquatic organisms displaying a cytotoxic response to the presence of toxic compounds. These organisms and assays are therefore not included in this overview.

Inducible systems, in contrast, have a low baseline luminescence, which increases after exposure to specific compounds ('lights on'). In these systems, both promoter and reporter genes may be inserted from other bacteria to give an optimal response to the compounds of interest. It should be noted however, that many inducible strains emit a low level of background luminescence when they are not induced. This enables the detection of high acute toxicity or other types of severe stress that may compromise the survival of the bacteria, as the background luminescence will then disappear [11]. However, when the background luminescence is on the high side, this tends to lower the sensitivity as it makes it harder to distinguish the signal [12].

Based on the promoters used in the construction of such "lights on" bioreporters, the inducible systems can be divided into effect- and compound-specific strains. The former respond to a specific type of toxicity, for example DNA damage, oxidative stress, or protein damage (heat shock). The compound-specific strains detect a single compound or group of compounds with similar chemical characteristics or mode of action, like specific metals, alkanes, or BTEX compounds (Figure 1) [11,13].




Figure 1. Overview of the luminescent bacterial reporter systems. The strains covered by this study are displayed in the 'Lights on' box

In summary, the aim of this review is to provide an overview of inducible, genetically engineered luminescent bioreporter bacteria, harbouring the *luxCDABE* genes (*lux* strains), which can potentially be integrated into a biosensor device. Several strains of these luminescent bacteria will be categorized and compared based on their inducers (and corresponding response). An evaluation is made of the characteristics that are important for water quality monitoring, e.g., sensitivity, response time, robustness, and pathogenicity.

2 Effect-specific *lux* strains

The effect-specific *lux* strains include strains that detect DNA, protein, and membrane damage, and oxidative stress. These strains are constructed by coupling the *luxCDABE* gene to a promoter that is involved in a specific stress response. As a result, the response of these strains is directly correlated with the total amount and potency of compounds that induce a specific type of stress.

DNA damage

Damage to DNA in bacteria can trigger at least two repair systems, the *ada*-controlled adaptive response specific to damage by alkylation, and the *recA*-dependent, *lexA*-controlled SOS response.

DNA damage by alkylation activates the *ada*-gene, which leads to transcription of the *ada*, *alkA*, *alkB*, and *aid* genes [14]. The SOS response can be induced by many chemicals that damage DNA, arrest DNA synthesis or arrest cell division, including mitomycin C (MMC), N-methyl-N'-nitro-N-nitrosoguanidine (MNNG), and methyl methane sulfonate (MMS). More than 40 genes are activated in the SOS response, including *recA*, *lexA*, *uvrA* and *umuDC* [15,14]. When the promoters of these genes are coupled to the *lux* gene, the extent of DNA damage can be easily measured as an increase in luminescence. In the majority of *lux* strains, *recA* is used as promoter. An overview of the strains used in the following studies can be found in Table 1.

Vollmer et al. (1997) compared three *lux* strains, DPD2794, DPD2818, and DPD2844, containing the promoters of the *recA*, *uvrA*, or *alkA* genes, respectively, fused to the *A. fischeri luxCDABE* genes. The best results were gained with DPD2844 (*alkA*), which showed the highest sensitivity (detection limit of <0.01 mg/l MNNG) and shortest response time (40-50 minutes). An important cause for the very high sensitivity was the very low background luminescence in this strain. It should be mentioned however, that not all strains were tested with the same compounds. For DPD2844, only results with MNNG were given, while for DPD2794 and DPD2818 detection limits for MMC and UV were displayed [16].

Davidov et al. (2000) conducted a study to improve the sensitivity of *recA* based DNA damage strains. The use of *luxCDABE* genes of *A. fischeri* resulted in a more sensitive, but slower response than *luxCDABE* from *Photobacterium luminescens*. The sensitivity was also improved by insertion of a single copy of the *recA::lux* fusion into the chromosome, instead of in multi-copy plasmids, and by a mutation in the *tolC* gene. Insertion in the chromosome resulted in a lower background luminescence, thus enhancing the ability to distinguish the signal. A *tolC* mutation impairs the ability of the cell to excrete toxicants, which leads to higher intracellular concentrations. These two adaptations resulted in strains with detection limits of 0.1 µg/l for MMC. In addition to the positive controls MMC, MNNG, and H₂O₂, also a group of other genotoxic and non-genotoxic compounds was tested. No false negatives were found, and except for one, all positives had been tested as potential genotoxicants in other bioassays [12].

As an alternative for the *E. coli* based strains, Elasmri and Miller (1998) developed strain RM4440, based on *Pseudomonas aeruginosa*. *P. aeruginosa* was chosen because it is a natural resident of water and soil, and as such, it was expected to be more robust than *E. coli* for on-line water monitoring. Strain RM4440 contained the *recA* and *luxCDABE* genes and was exposed to UV light. No limit of detection was mentioned, but lag times were about 30 minutes [17].

In a follow-up study by the same group, the same strain was exposed to 17 chemicals, of which eight are known SOS inducers. The cells were exposed in alginate beads to fixate them, as well as to simulate their own natural alginate biofilms. The *P. aeruginosa* reporter strain reacted to all compounds known to induce SOS in *E. coli* except H₂O₂ [18]. Suggested explanations were protection by the alginate or the ability of *P. aeruginosa* to actively degrade H₂O₂ [19]. A drawback of *P. aeruginosa* for use in environmental monitoring is that it is a known opportunistic human pathogen.

Hwang et al. (2008) constructed strain BBT*NrdA*, which is an *E. coli* based *lux* strain that has the *nrdA* gene as promoter. The *nrdA* gene is activated in DNA synthesis, but is not regulated by the SOS response. The strain reacted on all four DNA damaging agents tested (nalidixic acid, MMC, MNNG, and

4-nitroquinolin N-oxide). Also four phenolic compounds and four oxidative compounds were tested, but only one of these (H₂O₂) induced luminescence in this strain [20].

Conclusion

A large variety of DNA damage strains has been developed in the last decades, based upon a number of different promoters involved in DNA damage repair. The most sensitive *lux* strains found in this study were two modified *recA* strains, namely DPD2797 and DPD3063 [12].

Table 1. Literature overview of *lux* strains for the detection of DNA damage and their detection limits.

Strain	References	promoter	receiving strain	LOD	setup	Notes	
DPD2794	[21]	<i>recA</i>	RFM443	480 µg/l H ₂ O ₂	culture plate		
	[22]						portable sensor
	[12]				2 µg/l MMC		culture plate
	[23]				500 µg/l trimethoprin		culture plate
	[24]				optical fibre		
	[25]				10 µg/l MMC		bioreactor
	[26]				bioreactor		
	[27]				50 µg/l MMC		bioreactor
	[28]				5 µg/l MMC, 0.013 µg/l benzo[a]pyrene		flasks
	[29]				A-body plates		
[16]	100 µg/l MMC	culture plate					
DPD2797	[12]	<i>recA</i>	DE112	0.1 µg/l MMC	culture plate	<i>toIC</i> mutant	
	[30]						optical fibre
DPD1718	[12]	<i>recA</i>	DPD1692	100 µg/l MMC	culture plate	Chr.	
	[31]						optical fibre
	[32]						25 µg/l MMC
DPD1710	[33]	<i>recA</i>	RFM443	1 µg/l MMC	sol-gel wells	Chr.	
DPD1714	[12]	<i>recA</i>	DM800		culture plate	Chr.	
DPD1709	[12]	<i>recA</i>	DM803		culture plate	Chr.	
DPD3063	[12]	<i>recA</i>	W3110	0.1 µg/l MMC	culture plate	Chr.	
Sal94	[12]	<i>recA</i>	WG49	250 µg/l 4-nitrophenol	culture plate	<i>S. Typhimurium</i>	
RM4440	[17]	<i>recA</i>	FRD1		culture plate	<i>P. aeruginosa</i>	
	[18]						alginate beads
DPD2818	[16]	<i>uvrA</i>	RFM443	10 µg/l MMC	culture plate		
DPD2844	[16]	<i>alkA</i>	RFM443	<10 µg/l MMC	culture plate		
BBT <i>NrdA</i>	[20]	<i>NrdA</i>		156.3 µg/l MNNG	culture plate		

All strains are *E. coli* based with *luxCDABE* as reporter, unless stated otherwise under notes. chr. = genes are inserted in the chromosome, instead of plasmids.

LOD: Limit of Detection.

Protein damage

A mechanism found in cells of all organisms to counteract protein damage is the heat shock response. This response can be triggered by high temperatures, viral infections, exposure to various chemicals that react with proteins, and abnormal proteins resulting from other processes.

Van Dyk et al. (1994) used two promoters to develop *lux* strains for the detection of protein damage, namely the *grpE* gene and the *dnaKp* gene. The gene *dnaK* encodes for Hsp70, a heat-shock protein that has an important cellular function in protein folding and re-naturation. The gene *grpE* encodes for Hsp60, which has a similar function as Hsp70.

Both promoters responded to generally the same compounds, namely ethanol, methanol, copper sulphate, phenol and derivatives, and 2,4-dichlorophenoxyacetic acid, but *grpE* proved to be about 5- to 10-fold more sensitive. The *grpE* strain also had a higher basal luminescence level, and therefore it showed a lights-off effect at higher concentrations. Both lights-on and lights-off effects at high concentrations were enhanced in cells with a *tolC* mutation [34].

The *grpE* strain TV1061 has also been used in later studies, often incorporated in various setups (see Table 2). It has been shown to respond to a wider range of toxicants than any other *lux* strain, including phenols, halomethanes, oxidants, phosdrin, chlordimeform, sodium cyanide, and MNNG. However, it is less sensitive than for example DNA damage strains, with LOD's in the mg/l range. Human toxicants that did not induce TV1061 include colchicine, trimethylolpropane phosphate, nickel chloride, sodium selenite, and lindane [21,30].

Conclusion

Two promoter gene have been used to generate *lux* strains that are sensitive to protein damage. Of these, *grpE* gave the most sensitive strains (TV1061/TV1076), responded to a wide range of toxicants and has been used most often.

Table 2. Summary of strains for the detection of protein damage and their corresponding detection limits.

Strain	References	promoter	receiving strain	LOD	setup	Notes
TV1061	[21]	<i>grpE</i>	RFM443	0.1 mg/l 4-bromophenol	culture plate	
	[22]			<1% ethanol	portable sensor	
	[23]			5 mg/l rifampicin	culture plate	
	[24]				optical fibre	
	[25]			300 mg/l phenol	bioreactor	
	[26]				bioreactor	
	[35]				bioreactor	
	[33]			0.3% ethanol	sol-gel wells	
	[30]				optical fibre	
	[29]				A-body	
					glass/gold plates	
	[34]			±12 mg/l pentachlorophenol 1% ethanol	culture plate	
WM1202	[34]	<i>dnaKp</i>	RFM443	4% ethanol/ 19 mg/l pentachlorophenol	culture plate	
WM1302	[34]	<i>dnaKp</i>	DE112	50 mg/l phenol	culture plate	<i>tolC</i> mutant
TV1076	[34]	<i>grpE</i>	DE112	±0.07 mg/l pentachlorophenol	culture plate	<i>tolC</i> mutant

All strains are *E. coli* with *luxCDABE* as reporter.

Cell membrane damage

For compounds that cause cell membrane damage, bacteria can be used that contain the *fabA* gene, coupled to the full *lux* gene. The *fabA* gene codes for β -hydroxydecanoyl-ACP dehydrase and is responsible for the formation of double bonds in fatty acids which are used in the cell membrane. The *fabA* gene is activated by binding of the FadR protein, a process that is inhibited by long chain acyl-CoA thioesters. In case of membrane damage, fatty acid starvation will occur and long chain acyl-CoA thioester levels will be low, resulting in a high induction of *fabA*.

Strain DPD2540 containing *fabA* and *luxCDABE* was used in a study by Choi and Gu (1999) and was tested with several compounds. As expected, *fabA* was induced by membrane damaging agents, such as ethanol, phenol, and cerulenin. More surprisingly however, DPD2540 also responded to the DNA damaging agent MMC and the oxidative agent H₂O₂. The reason for this is probably that these agents also cause damage to the membrane as a secondary effect. In these cases the response was delayed from around 60 minutes for ethanol to 150 minutes for MMC and H₂O₂. Unfortunately, no detection limits were given in this study. [36]. For more studies that used this strain and other *fabA* strains, see Table 3.

A comparison of several *fabA* based *lux* strains was made by Bechor *et al.* (2002). The strains used included a *tolC* mutant (DPD2543), *fadR* mutant (DPD2549), and a strain with *fabA::lux* inserted in the chromosome (DPD1674). The *fadR* mutant gave almost no response, proving that the luminescence was indeed induced via *fabA*. The *tolC* mutant strain (DPD2543) was more sensitive for most of the tested chemicals than the non-mutant strain (DPD2544). However, this was not true for all membrane damaging substances. For example, DPD2543 was more sensitive to many phenol derivatives, but not to phenol itself.

The chromosomal insertion resulted in a drop in background luminescence of about a factor 100. DPD1674 had a higher response ratio for ethanol than DPD2544, but this was slightly lower for phenol. Whether the detection limit also differed was not clarified. Compounds that induced luminescence in *fabA* strains included alcohols, phenol and derivatives, halo-methanes, aromatics and detergents [37].

In comparisons between effect-specific *lux* strains, the *fabA* strains showed a close similarity to the protein damage strain (TV1061) in the compounds it responded to. Only in case of bromodichloromethane, paraquat, cumene hydroperoxide, and sodium cyanide, TV1061 was induced while the *fabA* strains failed to respond [21,30].

Conclusion

Several strains have been developed for the detection of membrane damage, all based on the *fabA* promoter. The amount of information on the sensitivity and specificity of these strains is limited, thus no preference for a strain could be entertained. Like the protein damage strains, they react on a broad range of compounds with detection limits in the mg/l range.

Table 3. Literature overview of *lux* strains for the detection of cell membrane damage and their detection limits.

Strain	References	promoter	receiving strain	LOD	setup	Notes
DPD2544	[37]	<i>fabA</i>	W3110	0.19 mg/l Triton X-100	culture plate	
	[29]				A-body glass/gold plates	
DPD2540	[37]	<i>fabA</i>	RFM443		culture plate	
	[21]		RFM444	0.14 mg/l	4-Bromophenol culture plate	
	[36]				culture plate	
	[22]				portable sensor	
	[25]			100 mg/l	phenol bioreactor	
	[26]				bioreactor	
	[35]				bioreactor	
DPD2543	[37]	<i>fabA</i>	DE112	0.08 mg/l	culture plate	<i>tolC</i>

Are luminescent bacteria suitable for online detection and monitoring of toxic compounds in drinking water and its sources?

BTO 2011.011

			4-nitrophenol		mutant
	[30]			optical fibre	
DPD2546	[37]	<i>fabA</i>	DC530	culture plate	
DPD2549	[37]	<i>fabA</i>	MH163	culture plate	
DPD1674	[37]	<i>fabA</i>	W3110	culture plate	Chr.

All strains are *E. coli* with *luxCDABE* as reporter. Chr. = genes are inserted in the chromosome, instead of by plasmids.

Oxidative stress

Active oxygen species are a serious threat to cells as they are capable of damaging proteins, nucleic acids, lipids, and membranes. Oxidative stress occurs naturally in cells as a result of respiration, or may be caused by toxic compounds. These toxicants can either generate peroxides (H_2O_2), superoxides ($O_2^{\bullet-}$) or hydroxyl radicals (OH^{\bullet}). Peroxides lead to the activation of the *E. coli* OxyR regulon, while superoxides induce SoxRS. Despite the fact that $O_2^{\bullet-}$ can also trigger the formation of OH^{\bullet}/H_2O_2 , most promoters are only activated by one of the two groups [38]. A large number of promoters from these pathways have been used to form *lux* strains that detect oxidative stress. In Table 4 a literature overview of these strains is given.

One of the genes under control of the OxyR regulon is *katG* (catalase hydroperoxidase I) [39]. Belkin et al. (1996) have introduced the *katG* promoter coupled to the full *luxCDABE* gene of *Vibrio fischeri* in *E. coli* resulting in strain DPD2511. Luminescence induction was found for several oxidative compounds, including H_2O_2 , organic peroxides, paraquat, menadione, xanthine, xanthine oxidase, and cigarette smoke. It also responded to ethanol and showed a synergistic response to the combination of ethanol and H_2O_2 [40]. Additionally, the same strain has been reported to respond to cadmium chloride, ethidium bromide, and bisphenol A. No response was seen after exposure to potassium dichromate [41].

DK1, a similar strain with *katG* as promoter also responded on H_2O_2 and menadione, but not on paraquat or structural analogs of paraquat [42].

The defence mechanism against superoxides, the SoxRS regulon, acts in two steps. Superoxide generating compounds are first detected by SoxR, which then induces transcription of SoxS, a transcriptional activator of 16 other genes. These include *sodA* (Mn-superoxide dismutase), *nfo* (DNA repair endonuclease IV), *zwf* (glucose-6-phosphate dehydrogenase), *acnA* (aconitase), *fumC* (stable fumarase), *fpr* (ferredoxin reductase), *acrAB* (efflux pumps), *micF* (antisense RNA for the *ompF* porin mRNA), and *fur* (repressor of iron transport) [39].

Several superoxide sensitive *lux* strains have been reported that are based on promoters from the SoxRS regulon, including DPD2515 (*micF*), EBSoxS (*soxS*), EBHJ (*sodA*), ZWF (*zwf*), DP1 (*pqi-5*), DS1 (*sodA*), EBFumC (*fumC*), and FPR (*fpr*) [21,41-44]. Reported inducers of these strains include paraquat (methyl viologen) and its structural analogs ethyl viologen, benzyl viologen and heptyl viologen. Exposure to hydroxyl radical or peroxides, like H_2O_2 , gave much lower or no responses [42,43,21]. Unfortunately, little is known about the sensitivity of these strains, although for DPD2515 and EBSoxS detection limits have been reported of about 0.01 mg/l paraquat [21,41].

In addition to the aforementioned strains, EBHmp (*hmp*) and PGRFM (*pqi*) have been developed, which contain promoters that belong neither to the OxyR or SoxRS pathway. PGRFM has been reported to respond to both superoxides and peroxides, with a lowest LOD of 0.6 mg/l for paraquat [38]. However, in another study both strains responded only to superoxides, namely paraquat, ethyl viologen, and heptyl viologen [42].

Conclusion

For the detection of all oxidative agents, both a superoxide and a peroxide sensing strain are needed. For peroxides, only *katG* based strains are available and relatively well

documented. For superoxides, a large array of strains has been constructed, but there is very limited information both on their sensitivity and selectivity.

Table 4. Literature overview of lux strains for the detection of oxidative stress and their detection limits.

Strain	References	reacts on	promoter	receiving strain	LOD	setup
DPD2511	[40]	peroxides	<i>katG</i>	RFM443	0.1 mg/l H ₂ O ₂	culture plate
	[21]					culture plate
	[22]					portable sensor
	[41]					culture plate
	[30]					optical fibre
	[29]					A-body glass/gold plates
DPD2515	[21]	superoxides	<i>micF</i>	W3110	0.01 mg/l paraquat	culture plate
	[29]					A-body glass/gold plates
DP1	[27]	superoxides	<i>pqi-5</i>	RFM443	0.1 mg/l paraquat	bioreactor
	[33]					sol-gel wells
PGRFM	[42]	superoxides	<i>pqi</i>	RFM443	0.6 mg/l paraquat	cell chip
	[38]					culture plate
DK1	[27]	peroxides	<i>katG</i>	RFM443	10 mg/l H ₂ O ₂	bioreactor
	[33]					sol-gel wells plate
	[45]					0.15% isopropanol 0.8 mg/l H ₂ O ₂
						0.88 µM (0.03 mg/l) H ₂ O ₂
EBSoxS	[44]	superoxides	<i>soxS</i>	RFM443		micro-fluid chip
DS1	[44]	superoxides	<i>sodA</i>	RFM443		cell chip
ZWF	[42]	superoxides	<i>zwf</i>	RFM443		cell chip
	[43]					culture plate
FPR	[42]	superoxides	<i>fpr</i>	RFM443		cell chip
	[43]					culture plate
EBFumC	[42]	superoxides	<i>fumC</i>	RFM443		cell chip
EBHmp	[42]	superoxides	<i>hmp</i>	RFM443		cell chip
EBHJ	[41]	superoxides	<i>sodA</i>	RFM443	0.015 mg/l paraquat	culture plate

All strains are *E. coli* with *luxCDABE* as reporter

3 Compound specific strains

In this section an overview is given of *lux* strains that respond specifically to certain types of compounds. These strains have been constructed by combining the *luxCDABE* reporter with promoter genes from bacteria that have developed an enhanced resistance to specific toxic compounds. Included are strains that respond to several types of organic pollutants and heavy metals. An overview of the strains for the detection of organic compounds is given in Table 5, and for metal sensing strains in Table 6.

BTEX compounds (Benzene, Toluene, Ethylbenzene, and Xylene)

For the monitoring of toluene and trichloroethylene (TCE) co-metabolism, strain B2 based on *Pseudomonas putida* was constructed by Applegate et al. (1997). *P. putida* is a non-pathogenic soil bacterium that is capable of utilizing and degrading organic solvents. This strain harbours the *tod-lux* complex that enables the detection of toluene and co-metabolised TCE. TCE is co-metabolic in the sense that it can not be used as a carbon source, but is degraded as a side effect. The *tod* operon encodes for a suite of enzymes that mediate the metabolism of toluene via the toluene dioxygenase complex. The strain had a limit of detection of 0.1 mg/l for toluene and a response time of 90 minutes. A strong response was also observed when the strain was exposed to jet fuel containing toluene [46]. Additionally to the aforementioned strain, the same group also constructed a strain with the same *tod-lux* complex inserted in the chromosome (TVA8). This resulted in higher sensitivity with a LOD of 30 µg/l, but a longer response time of 120 minutes. It was also responsive to benzene, ethylbenzene and *m*- and *p*-xylene, indicating that strains with the *tod* promoter can be used as a general BTEX monitor [47].

Naphthalene and salicylate

Naphthalene belongs to the polycyclic aromatic hydrocarbons (PAHs) and is a widely spread environmental pollutant. For the detection as well as the catabolism of naphthalene and its degradation intermediate salicylate,

Pseudomonas fluorescens strain HK44 was developed. *P. fluorescens* is a non-pathogenic bacterium that lives on plants, in water, and in soil. This strain harbours a fusion of the promoter of its own *nahG* gene for naphthalene degradation to *luxCDABE*. It responded in a dose dependant manner to both naphthalene and salicylate, with a LOD for naphthalene of 45 µg/l [48,49].

In a comparative study by Trogl et al. (2005) strain HK44 was exposed to 32 components other than naphthalene and salicylate. From the 32 compounds, it responded only to 2-aminobenzoic acid, salicylaldehyde, 4-methylsalicylic acid and, 4-chlorosalicylic acid [50].

The same strain, while immobilized in a sensor, also responded to jet fuel and contaminated soil extracts that contained naphthalene. Response times of 8 to 24 minutes were recorded in this setup. Toluene did not induce any measurable effects in these bacteria [51].

Two other strains based on a different naphthalene degradation pathway have been developed by Mitchell & Gu (2005). Both strains contain the *nagR-nagAa* gene promoters which are up-regulated by salicylate, coupled to *luxCDABE*. The first strain, called DNT5, has *E. coli* as host organism. The second strain, NAGK-1768, has *P. putida* as host organism which also possesses the ability to degrade naphthalene via the *nah* and *sal* operons. It was shown that, of the two strains, NAGK-1768 had the more favourable response characteristics with higher luminescence and a lower LOD for salicylic acid (4 µg/l, versus 331 µg/l in DNT5). NAGK-1768 also responded on 13 of 25 tested salicylic acid derivatives (also called salicylates) and naphthalene. DNT5 reacted on 5 of 25 salicylic acid derivatives [52].

In an additional study on the performance of DNT5 a slightly lower detection limit was reached then before (164 µg/l). The strain was also responsive to benzoic acid and two of its derivatives. Benzene, naphthalene, and phenol failed to induce a response [53].

Polychlorinated biphenyls (PCBs)

Layton et al. (1998) tested the PCB sensitive strain *Ralstonia eutropha* ENV307(pUTK60) containing the *orf0-bphA1* genes coupled to *luxCDABE*.

R. eutropha is a non-pathogenic bacterium that lives in soil and water and can degrade chloroaromatic compounds. The bacteria were exposed to biphenyl, monochlorinated biphenyls (CB) and Aroclor 1242

(PCB mixture) solutions. As the water-solubility of PCBs is very low, non-ionic surfactants were used to reach measurable concentrations in water. The highest sensitivity was reached with 4-chlorobiphenyl, which gave a detection limit of 0.15 mg/l. For Aroclor 1242 however, the detection limit was 1.5 mg/l, while the aqueous solubility without surfactants is <1 mg/l [54]. As these results indicate that as the concentrations PCBs in water will always be below LOD, the usefulness of this bacterial strain for in situ PCB monitoring in water is highly questionable.

Phenols

A strain for the detection of phenol and its methylated derivatives was developed by Leedjarv *et al.* (2006). The *dmpR* gene for catabolism of phenols was linked to *luxCDABE* and introduced in *P. fluorescens*. The lowest detection limits were found for 2-methylphenol (0.03 mg/l) and phenol (0.08 mg/l). Different phenols applied in a mixture caused an additive effect on the induction of the bacterial strain [55].

Table 5: Compound-specific lux strains for selective groups of organic chemicals and their detection limits.

Strain	species	References	reacts on	promoter	LOD	setup	Notes
B2	<i>P. putida</i>	[46]	toluene and TCE	<i>todC1C2BA</i>		vials and alginate beads	
TVA8	<i>P. putida</i>	[47]	all BTEX	<i>tod</i>	30 µg/l toluene	vials	Chr.
HK44	<i>P. fluorescens</i>	[56]				vials	
		[49]	naphthalene, salicylate	<i>nahG</i>	45 µg/l napht.	culture plate	
		[51]			550 µg/l napht.	sensor probe	
		[57]				sol-gel beads	
NAGK-1768	<i>P. putida</i>	[52]	naphthalene, salicylate	<i>nagR-nagAa</i>	4 µg/l salicylic acid	culture plate	
		[53]			164 µg/l salicylic acid	culture plate	
		[52]	salicylate	<i>nagR-nagAa</i>	331 µg/l salicylic acid	culture plate	
ENV307 (pUTK60)	<i>R. eutropha</i>	[54]	PCBs	<i>orf0-bphA1</i>	150 µg/l 4-CB	culture plate	
OS8 (pDNdmpRlux)	<i>P. fluorescens</i>	[55]	phenols	<i>dmpR</i>	30 µg/l 2-methylphenol, 80 µg/l phenol	culture plate	

All strains have *luxCDABE* as reporter, unless stated otherwise under notes. Chr. = genes are inserted in the chromosome, instead of plasmids.

Heavy metals

For the construction of metal sensing strains, the operons for metal resistance that some natural occurring bacteria possess are often used as promoters. For example the *mer* operon enables cells to convert Hg(II) to the less toxic Hg(0). The *ars* operon on the other hand, provides the ability to transport antimonite and arsenite out of the cell and to reduce arsenate to arsenite [58].

Unfortunately, no study was found in which an arsenic sensing strain was used that contains the complete luciferase gene. Since it is a very relevant metal for water monitoring, it was decided to include some studies that use strains that contain *luxAB* instead.

Stocker et al. (2003) used a regulatory gene from the *ars* operon, the *arsR* gene, combined with *luxAB* to construct a strain for the detection of arsenite. For this compound, it had a limit of detection of 4 µg/l and a response time of 30 minutes. The strain also responded to arsenate and antimony [59]. In a later study, the same strain was also used to determine arsenite in groundwater samples from Vietnam. The sensitivity in these samples was reduced somewhat by the presence of iron, which binds arsenite. It was determined that with 20 mg/l Fe the lowest detectable concentration was 7.5 µg/l, which is still below the WHO guideline value of 10 µg/l. In total 194 samples were tested, of which 112 samples were deemed safe. 8.0% was tested false negative and 2.4% false positive when compared with chemical analysis [60].

Two *E. coli* strains for the detection of various heavy metals were tested by Riether et al. (2001). The *pZNT::lux* strain proved to be sensitive to Cd(II), Pb(II), Zn(II), Hg(II), and to a lesser degree to Co(II), Ni(II), SbO₂, CrO₄²⁻, and Cr₂O₇²⁻. The strongest inducer of this strain was cadmium, with a detection limit of 10 nM (1.1 µg/l). The other strain tested was *pCOP::lux*, which reacted only to copper and silver, with detection limits of respectively 0.1 and 0.3-1 µM (11 and 19-64 µg/l). It was also verified that EDTA, and probably also other chelating components, lower the bioavailability of metals [61].

Three *E. coli* HB101 variants for the detection of mercury (HgII) were tested by Lyngberg et al. (1999). The largest dynamic range of detection for HgCl₂ was found with strain HB101(pRB28), which contains *merR* and a truncated form of *merT* (*merT'*). The highest sensitivity was found in cells immobilized in latex, which gave a detection limit of 0.1 nM HgCl₂ (27.2 ng/l) after 15 hours of induction. The detection limit was a factor 10 higher in suspended culture (1 nM or 0.27 µg/l), but the response time was reduced to one hour for the lowest concentration. In all cases, the lag time was drastically shortened at higher concentrations, although the suspended cells remained the fastest responders. It was also possible to enhance the response and sensitivity by adding cysteine, which increases mercury uptake. This resulted in a detection limit of 0.05 nM (13.6 ng/l) in immobilized cells [62].

Another strain for the detection of mercury which contains the *merR::luxCDABE* genes was constructed by Hakkila et al. (2002). The response time of this strain was 30 minutes. A limit of detection was not mentioned in this study [6]. The same strain was also tested during the EILATox-Oregon Workshop while it was immobilized in an alginate gel on the tip of a fibre. It reacted on mercury chloride, a river sample, and slightly on sodium cyanide [63].

A large comparative study was performed by Ivask et al. (2001) with 13 newly constructed metal-inducible strains with *luxCDABE* as reporter. Also 6 unspecific constitutive strains were tested as controls, to be able to recognize general toxic effects of the compounds. Special attention was given to the effect of other types of bacteria as host organisms: three strains were *E. coli*, eight strains *P. fluorescens*, one *Staphylococcus aureus*, and one *Bacillus subtilis* (Table 6). LODs were mostly in the microgram per litre range, with two mercury strains in the nanogram per litre range. Of the Gram-negative bacteria, *E. coli* was slightly more sensitive than *P. fluorescens*. Chromosomal insertion in the latter reduced background luminescence, but this did not lead to a higher sensitivity. Gram-positive bacteria were more difficult to modify, requiring a helper plasmid to prevent loss of the plasmid. They yielded quite similar LODs as the Gram-negative strains [64].

Table 6. Overview of metal specific strains and their detection limits.

Strain	species	References	reacts on	promoter	LOD	Notes
DH5a (pJAMA-arsR)	<i>E. coli</i>	[59] [60]	As, Sb	<i>arsR</i>	4 µg/l As 7.5 µg/l As	<i>luxAB</i> +20 mg/l Fe
MG1655 (pZNT-lux)	<i>E. coli</i>	[61]	Cd, Pb, Zn, Hg	<i>zntA</i>	1.1 µg/l Cd	
MG1655 (pCOP-lux)	<i>E. coli</i>	[61]	Cu(II), Ag(I)	<i>copA</i>	11 µg/l Ag	
HB101 (pRB28)	<i>E. coli</i>	[62]	Mercury	<i>merR-merT'</i>	0.0136 µg/l HgCl ₂	latex immob.
MC1061 (pmerRluxCDABE)	<i>E. coli</i>	[6] [63]	Hg	<i>merR</i>		optical fibre
MC1061(pmerR _{BS} BPmerlux)	<i>E. coli</i>	[64]	Hg, Cd	<i>merRB</i>	0.002 µg/l CH ₃ HgCl	
MC1061 (pSLzntR/pDNPzntAlux)	<i>E. coli</i>	[64]	Hg, Cd, Zn, Pb	<i>zntRA</i>	3 µg/l CdCl ₂	
MC1061 (pSLcueR/pDNPcopAlux)	<i>E. coli</i>	[64]	Cu, Ag	<i>copA</i>	20 µg/l CuSO ₄	
OS8 (pDNmerR _{BS} BPmerlux)	<i>P. fluorescens</i>	[64]	Hg, Cd	<i>merRB</i>	0.03 µg/l CH ₃ HgCl	
OS8 (pDNpbrRPpbrAlux)	<i>P. fluorescens</i>	[64]	Hg, Cd, Zn, Pb	<i>pbrRA</i>	40 µg/l HgCl ₂	
OS8 (pDNCadRPCadAlux)	<i>P. fluorescens</i>	[64]	Hg, Cd, Zn, Pb	<i>cadRA</i>	10 µg/l CdCl ₂	
OS8::KmerR _{BS} BPmerlux	<i>P. fluorescens</i>	[64]	Hg, Cd	<i>merRB</i>	0.8 µg/l HgCl ₂	Chr.
OS8::KncueRPcopAlux	<i>P. fluorescens</i>	[64]	Cu	<i>copA</i>	8000 µg/l CuSO ₄	Chr.
OS8::KnzntRPzntAlux	<i>P. fluorescens</i>	[64]	Hg, Cd, Zn, Pb	<i>zntRA</i>	20 µg/l CdCl ₂	Chr.
OS8::KnpbrRPpbrAlux	<i>P. fluorescens</i>	[64]	Hg, Cd, Zn, Pb	<i>pbrRA</i>	8 µg/l HgCl ₂	Chr.
OS9::KncadRPCadAlux	<i>P. fluorescens</i>	[64]	Hg, Cd, Zn, Pb	<i>cadRA</i>	5 µg/l HgCl ₂	Chr.
RN4220(pcadCPcadAlux)	<i>S. aureus</i>	[64]	Hg, Cd, Zn, Pb	<i>cadCA</i>	3 µg/l HgCl ₂	
BR151(pcadCPcadAlux)	<i>B. subtilis</i>	[64]	Hg, Cd, Zn, Pb	<i>cadCA</i>	2 µg/l CdCl ₂	

All strains have luxCDABE as reporter, unless stated otherwise under notes. With two exceptions, all experiments were performed on culture plates, for the exceptions, see notes. Chr. = genes are inserted in the chromosome, instead of plasmids.

4 Discussion

Biosensors based on luminescent bacteria may prove to be a valuable additional tool for the monitoring of water quality and safety. By combining different stress-responsive promoters with the bioluminescence genes, strains have been constructed that react with varying degrees of specificity to toxic effects (e.g., DNA damage), or specific groups of chemicals (e.g., heavy metals). The main purpose of this review is to evaluate available *lux* strains and their perspective for use in on-line water quality and safety monitoring. A preliminary selection was made upfront for strains with the bacterial *luxCDABE* genes, as this enables a fast response without the need for substrate addition.

An important factor in the evaluation of the strains is whether the measured effect or compound(s) can be expected to cause toxic effects in humans and whether they have additional value above already existing techniques. Since all strains in this review are genetically modified, strains should preferably be based on non-pathogenic bacteria to be allowed for use outside a laboratory. Another aspect that is taken into account is the sensitivity of the strains, which is compared to actual levels of contaminants that have been found in Dutch rivers, as well as drinking water standards. Unfortunately, in most cases little information is available on selectivity and specificity, which limits the possibility to compare strains on these parameters. The same lack of information exists for the robustness and stability of the bacteria when they are used over prolonged periods in natural water.

Effect-specific strains

Of all effects that can be detected by bacterial strains, DNA damage is probably the most relevant for humans. Because it is an effect that causes little acute damage, existing biomonitors are not very sensitive to compounds causing this effect. However, it can have severe consequences in humans on the long term.

A number of strains have been developed for the detection of DNA damage by coupling DNA repair genes to *luxCDABE*. To improve performance, some strains also contain different adjustments, like a *tolC* mutation or insertion of the genes in their chromosome. The most sensitive *lux* strains found in this study were two modified *recA* strains, namely DPD2797 and DPD3063 [12].

An important consideration when it comes to DNA damage that is rarely addressed is that many agents require metabolic activation before they become harmful to the DNA. This may be (partially) solved by adding rodent-derived cytochrome P450 (S9). However, in an on-line biosensor this is very impractical. Another option would be to incorporate some of these enzymes in the *lux* strains themselves as has been done already in *Salmonella typhimurium* for the umu-test (for an overview see [14]). These modifications are very appealing, but since there is a large variety of P450 enzymes involved and still very little experience with such strains it is unlikely that they will be used in on-line biosensors in the near future.

Both protein and membrane damage strains are also referred to as strains for general damage or stress, as they are relatively unspecific and have overlapping target components. As a result, these strains are expected to have less additional value above the existing biomonitors than for example DNA damage strains. Additionally, compounds that also cause other types of damage (e.g. MNNG, paraquat) can usually be detected more sensitively with strains that react specifically on these effects. On the other hand, in a system that employs multiple strains they may be very useful, as they detect toxicants that diminish the response in other, more specific strains [21,30].

For the detection of protein damage, strain TV1061 (*grpE::luxCDABE*) has probably the most favourable combination of sensitivity, specificity, and user experience [65]. As all membrane damage strains have the *fabA* gene as promoter, differences in sensitivity, selectivity, and response times between these strains are minor [37].

Oxidative stress differs somewhat from the aforementioned effects, as it causes damage in itself to DNA, proteins, and membranes. Thus it can be expected that compounds that cause oxidative stress will be detected to some extent by the aforementioned strains. However, by using genes from specific defence regulons as promoters, strains have been generated that have an enhanced sensitivity for oxidative

compounds. These strains can be divided in peroxide and superoxide sensing strains. Both types showed LODs of around 0.1 mg/l for respectively H₂O₂ and paraquat [44].

What might limit the usefulness of oxidative stress sensing strains in the field is the unstable nature of oxidative compounds. As no experimental field data is available on the occurrence of such compounds, it still has to be shown whether biosensors with these strains are of use.

Compound-specific strains

Additional to measuring a certain effect, one can also use a promoter that is activated in the presence of a specific compound or group of compounds. The advantage is that the detection limit for these compounds is usually lower in a compound-specific strain than in a strain that reports only the effect, often in the µg/l range. Because of their high specificity, they are generally less suitable for the monitoring of 'normal' surface or drinking water, as they are likely to miss many contaminations. However, in cases where only a specific type of contamination is of interest, they may be used as a fast and convenient detection method. Examples of such situations are after an incident or on (former) industrial sites [5]. The choice for a certain strain will in such situation mainly depend on the toxicants involved.

General remarks: comparability of studies referenced

A comment that needs to be made when attempting to compare the performance of such a diverse selection of reporter strains is that it is practically impossible to directly compare levels of luminescence between studies. Depending on the instrumentation used, different units are used to express light intensity. These are often completely arbitrary, and presented as instrument-specific RLU (Relative Light Unit), Ampere or SBL (Specific Bioluminescence in nAmp/OD) [47,36,30,66]. Another complicating factor is that the number of photons that corresponds with 1 RLU differs per photomultiplier, even if they are of the same type and manufacturer.

However, most performance criteria can be calculated regardless of the units of luminescence used. The most common way to do this is by using response ratios to quantify the signal, which are defined as the ratio of luminescence relative to the un-induced control [21]. The disadvantage of this method is that response ratios are strongly influenced by the background luminescence. As a result, the relationship between response ratios and actual luminescence differs per strain, with in general lower maximal response ratios in strains with high background luminescence [67,64]. Most studies with response ratios also give a graph with the luminescence levels in RLU's, to give some insight in the absolute difference between signal and background [12]. Another possibility is to use the absolute difference in luminescence between background and induced cells [67].

The Limit of Detection has also been determined in several different manners. If response ratios are used, the LOD is usually defined as the concentration that leads to a two fold induction of luminescence over the background, i.e. a response ratio of two [37]. In studies that express light intensity in RLUs, the LOD is often defined as the concentration that leads to a significantly higher luminescence compared with the control [68]. It should be mentioned that the LOD is not only dependent on the strain, but also the inducer, cell concentration, bioavailability, measurement time and operational protocol. These differences in determining induction and LODs should be kept in mind when comparing studies, especially when the differences are relatively small. In this study, the LODs given have been determined by the original authors of the studies. However, for the comparisons between studies only differences in LOD of a factor of ten or more for the same component are considered relevant.

A similar observation may be made concerning the determination of response or lag times, which are highly dependent on the concentrations used. Nevertheless it can be said that, on average most lag times are around 60 minutes, with a few fast responders of 30 minutes or less and slow responders of 90 minutes or more. In case of an on-line biosensor that is used as an early warning system in surface water, a response time of around one hour will usually be fast enough for detecting passing contamination peaks. There will then be enough time to react to an alarm from the sensor, before the contaminated water reaches the treatment plant inlet or ultimately the consumers as drinking water. For alarm monitoring of drinking water in distribution networks, naturally, response times will have to be much shorter.

Biosensing pollutants in surface water

The most important question that remains is whether these bacteria can actually detect the levels of toxicants that occur in reality. To truly answer this question, it would be necessary to perform field studies. However, an estimate can be made by comparing the LODs with peak levels of compounds of concern that have been found recently in surface water, and with the target values for contaminants of drinking water.

A large number of studies have been performed to determine levels of pollutants in surface water, of which a few examples will be given. A survey was performed by Loos et al. (2009) to determine the occurrence of polar organic pollutants in European rivers. The highest concentrations measured were 31 µg/l ibuprofen, 39.8 µg/l caffeine, 19.4 µg/l tolyltriazole, and 11.6 µg/l carbamazepine [69].

In the Netherlands, measurements have also been taken after large spills. There were 49 large spills reported in 2008 in the Rhine, of which most involved BTEX compounds, MTBE (methyl tertiary butyl ether), ETBE (ethyl tert-butylether), or a combination of these substances. The highest concentration measured after an incident was 91 µg/l trichloromethane. The peak concentrations measured in routine measurements were generally lower, for example 6.0 µg/l MTBE (Nieuwegein), 2.58 µg/l ETBE (Lobith), 1.3 µg/l toluene (Nieuwegein), and 7.8 µg/l lead (Nieuwegein) [70].

In two recent literature surveys, emerging contaminants and trace pollutants were evaluated on their occurrence and toxicity [71,72]. The highest priority was given to compounds that are both a human health hazard and are frequently detected in surface water. In table 7 a summary of the highest ranking compounds is displayed.

Table 7. High priority emerging contaminants and trace pollutants.

Compound	Common use	Max conc	Location	Reference
Carbamazepine	Anticonvulsant	12	EU	[69]
1,4-dioxane	Solvent	10	EU	[72]
17 α-ethinyl estradiol (EE2)	Hormone	0.83	US	[73]
17 β-estradiol	Hormone	0.2	US	[73]
Estrone	Hormone	0.11	US	[73]
Perfluorooctanic acid (PFOA)	Water proofing	19	US	[74]
Perfluorooctanesulfonic acid (PFOS)	Water proofing	1.4	EU	[69]
Bis(2-ethylhexyl)phthalate	Plasticizer	98	EU	[75]
Diazinon	Insecticide	1.1	US	[76]
Methoxychlor	Herbicide	1.7	EU	[77]
Dieldrin	Insecticide	0.21	US	[73]
N,N-diethyl-meta-tolamide (DEET)	Insect repellent	1.1	US	[73]
Triclosan	Antiseptic	2.3	US	[73]
Acetaminophen	Pain reliever	10	US	[73]

All concentrations are in µg/l.

The WHO (World Health Organization) has set guideline values for drinking water for some chemicals, including arsenic (10 µg/l), cadmium (3 µg/l), mercury (6 µg/l), and toluene (700 µg/l) [78]. These levels can be detected with strains specific for these compounds. However, there for the majority of the detected compounds, no specific guideline values have been determined yet. With analytical methods becoming more and more sensitive, the number of contaminants detected in drinking water is increasing, while their levels are mostly not of any health concern. Recently, target values have been set by the Dutch drinking water industry to define what levels of contaminants are acceptable from both a human health perspective, as well as from an ethical or esthetical perspective. This latter perspective stems from the philosophy that contaminants do not belong in drinking water. Based on the Thresholds

of Toxicological Concern (TTCs) set for food additives and on the opinions of Dutch drinking water experts of what is ethically acceptable, target values of 0.01 µg/l for genotoxic contaminants and 0.1 µg/l for other contaminants have been derived [72,79,1].

When compared to the TTC derived target values for drinking water, the detection thresholds of both effect- and compound-specific strains are generally too high to be used for monitoring. The only exceptions are the strains for the detection of mercury with a lowest LOD of 0.002 µg/l for methyl mercury [64].

However, the peak concentrations that have been measured in surface water are much higher, as is also expected to be the case after intentional water poisoning. In these cases, sensors based on *lux* strains may be very useful to detect spills in an early stage, provide an early warning of such events and prevent the intake of contaminated water.

Additionally, there are also various efforts being undertaken to improve the sensitivity of luminescent strains by using different or additional modifications. The insertion of the promoter-reporter genes in the chromosome and the addition of a *tolC* mutation have already been mentioned. In an article in this same special issue, Yagur-Kroll and Belkin demonstrate that both the sensitivity and response times can also be improved by splitting the *luxCDABE* genes in two separately controlled units. The best effect was gained when *luxAB* (the luciferase enzyme) was inducible by a promoter and *luxCDE* (the aldehyde substrate) was expressed constitutively [80].

What also should be noted is that contaminations often consist of mixtures of compounds. Compounds exerting a similar type of effect through a similar mode of action often behave additively in mixtures, but sometimes synergism and antagonism can also occur with compounds with a different mode of action, interfering with the effects observed. Depending on the strain and compounds involved, this can lead to either improvement or reduction of the ability of the bacteria to detect the collective activity of a complex mixture as a sum parameter. At this moment, little is known about the significance of these mixture reactions for *lux* strains.

Another issue that is of great importance for the application of biosensors is the ability of the bacteria to remain alive and active in natural water. This is of course also dependent on the design of the sensor and the matrix in which the bacteria are contained. Nevertheless, differences in robustness between species of bacteria can be expected.

So far, most studies have been performed with *E. coli* K12, as these are non-pathogenic and relatively easy to modify. Since *E. coli* is originally an inhabitant of the intestine, it is not very robust when exposed to natural water. Several studies have shown that especially the presence of other microorganisms is detrimental for the survival of *E. coli* in unsterilized water [81-83].

However, very few other species have been used to construct *lux* strains. Only for the detection of organic pollutants like toluene and naphthalene it is common to use different bacteria, like the natural soil bacteria *P. putida* and *P. fluorescense* [46,51,84]. *P. fluorescense* has also been used in the development of metal sensing strains, while *cadA* combined with *luc* or *luxCDABE* has been brought into *B. subtilis* and *S. aureus*. Of these two, *S. aureus* is a common resident of human skin, while *B. subtilis* is a non-pathogenic soil bacterium [85,64].

Although these bacteria are generally no more sensitive than *E. coli*, they might be more robust as water is often their natural habitat, which makes it likely they will remain active over a longer time. However, it still has to be confirmed whether they indeed yield better results in an on-line sensor.

5 Conclusion

A large number of luminescent bacteria have been developed for the detection of various toxic effects and compounds. Although most studies so far have been performed in the laboratory, implementation in a biosensor in the field holds the highest promise for these bacteria. The currently existing strains have detection thresholds that range from mg/l to $\mu\text{g/l}$. In general, more specific strains tend to be more sensitive. Since peak concentrations after incidents in Dutch rivers are generally in the low $\mu\text{g/l}$ range, only a few strains will be capable of detecting individual compounds. Sensitivity improvement is therefore necessary. Nevertheless, these strains may have added value above existing techniques in the detection of mixtures of toxicants and in early warning systems. Other issues that need to be addressed in case of field use include response times, robustness, signal quantification, and pathogenicity.

6 Acknowledgments

This work was performed in the TTIW-cooperation framework of Wetsus, Centre of Excellence for Sustainable Water Technology (www.wetsus.nl). Wetsus is funded by the Dutch Ministry of Economic Affairs. The authors like to thank the participants of the Sensoring research theme for the fruitful discussions and their financial support.

7 References

1. Wezel van A, Mons M, Delft van W (2009) New methods to monitor emerging chemicals in the drinking water production chain. *Journal of Environmental Monitoring*:1-11. doi:10.1039/b912979k
2. Lowe CR (2007) Overview of biosensor and bioarray technologies. In: Marks RS, Cullen DC, Karube I, Lowe CR, Weetall HH (eds) *Handbook of biosensors and biochips*, vol 1. John Wiley & Sons Ltd, Chichester, pp 7-22
3. van der Meer JR, Tropel D, Jaspers M (2004) Illuminating the detection chain of bacterial bioreporters. *Environmental Microbiology* 6 (10):1005-1020. doi:10.1111/j.1462-2920.2004.00655.x
4. van der Meer JR, Belkin S (2010) Where microbiology meets microengineering: Design and applications of reporter bacteria. *Nat Rev Micro* 8 (7):511-522
5. Sagi E, Hever N, Rosen R, Bartolome AJ, Premkumar JR, Ulber R, Lev O, Scheper T, Belkin S (2003) Fluorescence and bioluminescence reporter functions in genetically modified bacterial sensor strains. *Sensors and Actuators B-Chemical* 90 (1-3):2-8. doi:10.1016/s0925-4005(03)00014-5
6. Hakkila K, Maksimow M, Karp M, Virta M (2002) Reporter genes *lucff*, *luxcdabe*, *gfp*, and *dsred* have different characteristics in whole-cell bacterial sensors. *Analytical Biochemistry* 301 (2):235-242. doi:10.1006/abio.2001.5517
7. Li YF, Li FY, Ho CL, Liao VHC (2008) Construction and comparison of fluorescence and bioluminescence bacterial biosensors for the detection of bioavailable toluene and related compounds. *Environmental Pollution* 152 (1):123-129. doi:10.1016/j.envpol.2007.05.002
8. Keane A, Phoenix P, Ghoshal S, Lau PCK (2002) Exposing culprit organic pollutants: A review. *Journal of Microbiological Methods* 49 (2):103-119
9. Daniel R, Almog R, Ron A, Belkin S, Diamand YS (2008) Modeling and measurement of a whole-cell bioluminescent biosensor based on a single photon avalanche diode. *Biosensors and Bioelectronics*. doi:10.1016/j.bios.2008.07.026
10. Billard P, DuBow MS (1998) Bioluminescence-based assays for detection and characterization of bacteria and chemicals in clinical laboratories. *Clinical Biochemistry* 31 (1):1-14
11. Gu MB, Mitchell RJ, Kim BC (2004) Whole-cell-based biosensors for environmental biomonitoring and application. *Adv Biochem Engin/Biotechnol* 87:269-305. doi:10.1007/b13533
12. Davidov Y, Rozen R, Smulski DR, Van Dyk TK, Vollmer AC, Elsemore DA, LaRossa RA, Belkin S (2000) Improved bacterial *sos* promoter:: Lux fusions for genotoxicity detection. *Mutation Research-Genetic Toxicology and Environmental Mutagenesis* 466 (1):97-107
13. Belkin S (2003) Microbial whole-cell sensing systems of environmental pollutants. *Current Opinion in Microbiology* 6 (3):206-212. doi:10.1016/s1369-5274(03)00059-6

14. Biran A, Yagur-Kroll S, Pedahzur R, Buchinger S, Reifferscheid G, Ben-Yoav H, Shacham-Diamand Y, Belkin S (2009) Bacterial genotoxicity bioreporters. *Microbial Biotechnology*. doi:10.1111/j.1751-7915.2009.00160.x
15. Janion C (2008) Inducible sos response system of DNA repair and mutagenesis in *Escherichia coli*. *International Journal of Biological Sciences* 4 (6):338-344
16. Vollmer AC, Belkin S, Smulski DR, VanDyk TK, LaRossa RA (1997) Detection of DNA damage by use of *Escherichia coli* carrying *recA'-lux*, *uvrA'-lux*, or *alkA'-lux* reporter plasmids. *Applied and Environmental Microbiology* 63 (7):2566-2571
17. Elasri MO, Miller RV (1998) A *Pseudomonas aeruginosa* biosensor responds to exposure to ultraviolet radiation. *Applied Microbiology and Biotechnology* 50 (4):455-458
18. Elasri MO, Reid T, Hutchens S, Miller RV (2000) Response of a *Pseudomonas aeruginosa* biofilm community to DNA-damaging chemical agents. *FEMS Microbiology Ecology* 33 (1):21-25
19. Elkins JG, Hassett DJ, Stewart PS, Schweizer HP, McDermott TR (1999) Protective role of catalase in *Pseudomonas aeruginosa* biofilm resistance to hydrogen peroxide. *Applied and Environmental Microbiology* 65 (10):4594-4600
20. Hwang ET, Ahn JM, Kim BC, Gu MB (2008) Construction of a *nrda :: Luxcdabe* fusion and its use in *Escherichia coli* as a DNA damage biosensor. *Sensors* 8 (2):1297-1307
21. Belkin S, Smulski DR, Dadon S, Vollmer AC, Van Dyk TK, Larossa RA (1997) A panel of stress-responsive luminous bacteria for the detection of selected classes of toxicants. *Water Research* 31 (12):3009-3016
22. Choi SH, Gu MB (2002) A portable toxicity biosensor using freeze-dried recombinant bioluminescent bacteria. *Biosensors & Bioelectronics* 17 (5):433-440
23. Eltzov E, Ben-Yosef DZ, Kushmaro A, Marks R (2008) Detection of sub-inhibitory antibiotic concentrations via luminescent sensing bacteria and prediction of their mode of action. *Sensors and Actuators B-Chemical* 129 (2):685-692. doi:10.1016/j.snb.2007.09.054
24. Eltzov E, Marks RS, Voost S, Wullings BA, Heringa MB (2009) Flow-through real time bacterial biosensor for toxic compounds in water. *Sensors and Actuators B: Chemical* 142 (1):11-18
25. Kim BC, Gu MB (2005) A multi-channel continuous water toxicity monitoring system: Its evaluation and application to water discharged from a power plant. *Environmental Monitoring and Assessment* 109 (1-3):123-133. doi:10.1007/s10661-005-5843-7
26. Kim BC, Gu MB, Hansen PD (2005) Evaluation of water-borne toxicity using bioluminescent bacteria. In: Lichtfouse E, Schwarzbauer J, Didier R, Eds. (eds) *Environmental chemistry: Green chemistry and pollutants in ecosystems*. Springer, Berlin,
27. Lee JH, Gu MB (2005) An integrated mini biosensor system for continuous water toxicity monitoring. *Biosensors & Bioelectronics* 20 (9):1744-1749. doi:10.1016/j.bios.2004.06.036

28. Min J, Kim EJ, LaRossa RA, Gu MB (1999) Distinct responses of a *recA::Luxcdabe* *escherichia coli* strain to direct and indirect DNA damaging agents. *Mutation Research/Genetic Toxicology and Environmental Mutagenesis* 442 (2):61-68
29. Premkumar JR, Lev O, Marks RS, Polyak B, Rosen R, Belkin S (2001) Antibody-based immobilization of bioluminescent bacterial sensor cells. *Talanta* 55 (5):1029-1038
30. Pedahzur R, Polyak B, Marks RS, Belkin S (2004) Water toxicity detection by a panel of stress-responsive luminescent bacteria. *Journal of Applied Toxicology* 24 (5):343-348. doi:10.1002/jat.1023
31. Polyak B, Bassis E, Novodvoretz A, Belkin S, Marks RS (2000) Optical fiber bioluminescent whole-cell microbial biosensors to genotoxicants. *Water Science and Technology* 42 (1-2):305-311
32. Polyak B, Bassis E, Novodvoretz A, Belkin S, Marks RS (2001) Bioluminescent whole cell optical fiber sensor to genotoxicants: System optimization. *Sensors and Actuators B-Chemical* 74 (1-3):18-26
33. Mitchell RJ, Gu MB (2006) Characterization and optimization of two methods in the immobilization of 12 bioluminescent strains. *Biosensors & Bioelectronics* 22 (2):192-199. doi:10.1016/j.bios.2005.12.019
34. Van Dyk TK, Majarian WR, Konstantinov KB, Young RM, Dhurjati PS, Larossa RA (1994) Rapid and sensitive pollutant detection by induction of heat-shock gene-bioluminescence gene fusions. *Applied and Environmental Microbiology* 60 (5):1414-1420
35. Lee JH, Song CH, Kim BC, Gu MB (2006) Application of a multi-channel system for continuous monitoring and an early warning system. *Water Science and Technology* 53 (4-5):341-346. doi:10.2166/wst.2006.139
36. Choi S, Gu M (1999) A whole cell bioluminescent biosensor for the detection of membrane-damaging toxicity. *Biotechnology and Bioprocess Engineering* 4 (1):59-62
37. Bechor O, Smulski DR, Van Dyk TK, LaRossa RA, Belkin S (2002) Recombinant microorganisms as environmental biosensors: Pollutants detection by *escherichia coli* bearing *faba'*: *Lux* fusions. *Journal of Biotechnology* 94 (1):125-132
38. Niazi JH, Kim BC, Ahn JM, Gu MB (2008) A novel bioluminescent bacterial biosensor using the highly specific oxidative stress-inducible *pgi* gene. *Biosensors & Bioelectronics* 24 (4):670-675. doi:10.1016/j.bios.2008.06.026
39. Asad NR, Asad L, de Almeida CEB, Felzenszwalb I, Cabral-Neto JB, Leitao AC (2004) Several pathways of hydrogen peroxide action that damage the *e-coli* genome. *Genetics and Molecular Biology* 27 (2):291-303
40. Belkin S, Smulski DR, Vollmer AC, VanDyk TK, LaRossa RA (1996) Oxidative stress detection with *escherichia coli* harboring a *katg'*:*Lux* fusion. *Applied and Environmental Microbiology* 62 (7):2252-2256
41. Lee HJ, Gu MB (2003) Construction of a *soda* :: *Luxcdabe* fusion *escherichia coli*: Comparison with a *katg* fusion strain through their responses to oxidative stresses. *Applied Microbiology and Biotechnology* 60 (5):577-580. doi:10.1007/s00253-002-1168-4

42. Lee JH, Youn CH, Kim BC, Gu MB (2007) An oxidative stress-specific bacterial cell array chip for toxicity analysis. *Biosensors & Bioelectronics* 22 (9-10):2223-2229. doi:10.1016/j.bios.2006.10.038
43. Niazi JH, Kim BC, Gu MB (2007) Characterization of superoxide-stress sensing recombinant escherichia coli constructed using promoters for genes zwf and fpr fused to lux operon. *Applied Microbiology and Biotechnology* 74 (6):1276-1283. doi:10.1007/s00253-006-0758-y
44. Lee JH, Mitchell RJ, Kim BC, Cullen DC, Gu MB (2005) A cell array biosensor for environmental toxicity analysis. *Biosensors & Bioelectronics* 21 (3):500-507. doi:10.1016/j.bios.2004.12.015
45. Yoo SK, Lee JH, Yun SS, Gu MB (2007) Fabrication of a bio-mems based cell-chip for toxicity monitoring. *Biosensors & Bioelectronics* 22 (8):1586-1592. doi:10.1016/j.bios.2006.07.014
46. Applegate B, Kelly C, Lackey L, McPherson J, Kehrmeyer S, Menn FM, Bienkowski P, Saylor G (1997) *Pseudomonas putida* b2: A tod-lux bioluminescent reporter for toluene and trichloroethylene co-metabolism. *Journal of Industrial Microbiology & Biotechnology* 18 (1):4-9
47. Applegate BM, Kehrmeyer SR, Saylor GS (1998) A chromosomally based tod-luxcdabe whole-cell reporter for benzene, toluene, ethylbenzene, and xylene (bTEX) sensing. *Appl Environ Microbiol* 64 (7):2730-2735
48. Webb OF, Bienkowski PR, Matrubutham U, Evans FA, Heitzer A, Saylor GS (1997) Kinetics and response of a *Pseudomonas fluorescens* hk44 biosensor. *Biotechnology and Bioengineering* 54 (5):491-502
49. Heitzer A, Webb OF, Thonnard JE, Saylor GS (1992) Specific and quantitative assessment of naphthalene and salicylate bioavailability by using a bioluminescent catabolic reporter bacterium. *Applied and Environmental Microbiology* 58 (6):1839-1846
50. Trogl J, Ripp S, Kuncova G, Saylor GS, Churava A, Parik P, Demnerova K, Halova J, Kubickova L (2005) Selectivity of whole cell optical biosensor with immobilized bioreporter *Pseudomonas fluorescens* hk44. *Sensors and Actuators B-Chemical* 107 (1):98-103. doi:10.1016/j.snb.2004.07.039
51. Heitzer A, Malachowsky K, Thonnard JE, Bienkowski PR, White DC, Saylor GS (1994) Optical biosensor for environmental online monitoring of naphthalene and salicylate bioavailability with an immobilized bioluminescent catabolic reporter bacterium. *Applied and Environmental Microbiology* 60 (5):1487-1494
52. Mitchell RJ, Gu MB (2005) Construction and evaluation of nagr-nagaa :: Lux fusion strains in biosensing for salicylic acid derivatives. *Applied Biochemistry and Biotechnology* 120 (3):183-197
53. Lee JH, Mitchell RJ, Gu MB (2007) Chemical-specific continuous biomonitoring using a recombinant bioluminescent bacterium dnt5 (nagr-nagaa :: Luxcdabe). *Journal of Biotechnology* 131 (3):330-334. doi:10.1016/j.jbiotec.2007.06.020
54. Layton AC, Muccini M, Ghosh MM, Saylor GS (1998) Construction of a bioluminescent reporter strain to detect polychlorinated biphenyls. *Applied and Environmental Microbiology* 64 (12):5023-5026

55. Leedjarv A, Ivask A, Virta M, Kahru A (2006) Analysis of bioavailable phenols from natural samples by recombinant luminescent bacterial sensors. *Chemosphere* 64 (11):1910-1919. doi:10.1016/j.chemosphere.2006.01.026
56. Bhattacharyya J, Read D, Amos S, Dooley S, Killham K, Paton GI (2005) Biosensor-based diagnostics of contaminated groundwater: Assessment and remediation strategy. *Environmental Pollution* 134 (3):485-492. doi:10.1016/j.envpol.2004.09.002
57. Matrubutham U, Thonnard JE, Saylor GS (1997) Bioluminescence induction response and survival of the bioreporter bacterium *Pseudomonas fluorescens* hk44 in nutrient-deprived conditions. *Applied Microbiology and Biotechnology* 47 (5):604-609
58. Ramanathan S, Ensor M, Daunert S (1997) Bacterial biosensors for monitoring toxic metals. *Trends in Biotechnology* 15 (12):500-506
59. Stocker J, Balluch D, Gsell M, Harms H, Feliciano J, Daunert S, Malik KA, Van der Meer JR (2003) Development of a set of simple bacterial biosensors for quantitative and rapid measurements of arsenite and arsenate in potable water. *Environmental Science & Technology* 37 (20):4743-4750. doi:10.1021/es034258b
60. Trang PTK, Berg M, Viet PH, Van Mui N, Van Der Meer JR (2005) Bacterial bioassay for rapid and accurate analysis of arsenic in highly variable groundwater samples. *Environmental Science & Technology* 39 (19):7625-7630. doi:10.1021/es050992e
61. Riether KB, Dollard MA, Billard P (2001) Assessment of heavy metal bioavailability using *Escherichia coli* zntap :: Lux and copap :: Lux-based biosensors. *Applied Microbiology and Biotechnology* 57 (5-6):712-716
62. Lyngberg OK, Stemke DJ, Schottel JL, Flickinger MC (1999) A single-use luciferase-based mercury biosensor using *Escherichia coli* hb101 immobilized in a latex copolymer film. *Journal of Industrial Microbiology & Biotechnology* 23 (1):668-676
63. Hakkila K, Green T, Leskinen P, Ivask A, Marks R, Virta M (2004) Detection of bioavailable heavy metals in eilatox-oregon samples using whole-cell luminescent bacterial sensors in suspension of immobilized onto fibre-optic tips. *Journal of Applied Toxicology* 24:333-342. doi:10.1002/jat.1020
64. Ivask A, Rolova T, Kahru A (2009) A suite of recombinant luminescent bacterial strains for the quantification of bioavailable heavy metals and toxicity testing. *BMC Biotechnology* 9 (41). doi:10.1186/1472-6750-9-41
65. Vandyk TK, Majarian WR, Konstantinov KB, Young RM, Dhurjati PS, Larossa RA (1994) Rapid and sensitive pollutant detection by induction of heat-shock gene-bioluminescence gene fusions. *Applied and Environmental Microbiology* 60 (5):1414-1420
66. Vijayaraghavan R, Islam SK, Zhang M, Ripp S, Caylor S, Bull ND, Moser S, Terry SC, Blalock BJ, Saylor GS (2007) A bioreporter bioluminescent integrated circuit for very low-level chemical sensing in both gas and liquid environments. *Sensors and Actuators B-Chemical* 123 (2):922-928. doi:10.1016/j.snb.2006.10.064
67. Yagur-Kroll S, Bilic B, Belkin S (2009) Strategies for enhancing bioluminescent bacterial sensor performance by promoter region manipulation. *Microbial Biotechnology* 9999 (9999)
68. Sticher P, Jaspers MCM, Stemmler K, Harms H, Zehnder AJB, van der Meer JR (1997) Development and characterization of a whole-cell bioluminescent sensor for bioavailable

middle-chain alkanes in contaminated groundwater samples. *Applied and Environmental Microbiology* 63 (10):4053-4060

69. Loos R, Gawlik BM, Locoro G, Rimaviciute E, Contini S, Bidoglio G (2009) Eu-wide survey of polar organic persistent pollutants in european river waters. *Environmental Pollution* 157 (2):561-568

70. Rijnwaterbedrijven R (2008) Jaarrapport 2008 de rijn. RIWA-Rijn, Vereniging van Rivierwaterbedrijven, Nieuwegein

71. Murray KE, Thomas SM, Bodour AA (2010) Prioritizing research for trace pollutants and emerging contaminants in the freshwater environment. *Environmental Pollution*

72. Schriks M, Heringa MB, van der Kooij MME, de Voigt P, van Wezel AP (2010) Toxicological relevance of emerging contaminants for drinking water quality. *Water Research* 44 (2):461-476

73. Kolpin DW, Furlong ET, Meyer MT, Thurman EM, Zaugg SD, Barber LB, Buxton HT (2002) Pharmaceuticals, hormones, and other organic wastewater contaminants in us streams, 1999-2000: A national reconnaissance. *Environmental Science & Technology* 36 (6):1202-1211. doi:10.1021/es011055j

74. Fromme H, Tittlemier SA, Völkel W, Wilhelm M, Twardella D (2009) Perfluorinated compounds - exposure assessment for the general population in western countries. *International Journal of Hygiene and Environmental Health* 212 (3):239-270

75. Fromme H, Kächler T, Otto T, Pilz K, Müller J, Wenzel A (2002) Occurrence of phthalates and bisphenol a and f in the environment. *Water Research* 36 (6):1429-1438

76. Kolpin DW, Skopec M, Meyer MT, Furlong ET, Zaugg SD (2004) Urban contribution of pharmaceuticals and other organic wastewater contaminants to streams during differing flow conditions. *Science of the Total Environment* 328 (1-3):119-130

77. Badach H, Nazimek T, Kamiński R, Turski WA (2000) Organochlorine pesticides concentration in the drinking water from regions of extensive agriculture in poland. *Annals of Agricultural and Environmental Medicine* 7 (1):25-28

78. WHO (2008) Guidelines for drinking-water quality, vol 1. third edition incorporating the first and second Addenda, Recommendations edn., Geneva, Switzerland

79. Kroes R, Renwick AG, Cheeseman M, Kleiner J, Mangelsdorf I, Piersma A, Schilter B, Schlatter J, van Schothorst F, Vos JG, Wurtzen G (2004) Structure-based thresholds of toxicological concern (ttc): Guidance for application to substances present at low levels in the diet. *Food and Chemical Toxicology* 42 (1):65-83. doi:10.1016/j.fct.2003.08.006

80. Yagur-kroll S, Belkin S (in press) Upgrading bioluminescent bacterial bioreporter performance by splitting the *lux* operon. *Anal Bioanal Chem*. doi:10.1007/s00216-010-4266-7

81. Gordon C, Toze S (2003) Influence of groundwater characteristics on the survival of enteric viruses. *Journal of Applied Microbiology* 95 (3):536-544. doi:10.1046/j.1365-2672.2003.02010.x

82. Bogosian G, Sammons LE, Morris PJJ, Oneil JP, Heitkamp MA, Weber DB (1996) Death of the escherichia coli k-12 strain w3110 in soil and water. *Applied and Environmental Microbiology* 62 (11):4114-4120
83. Brettar I, Hofle MG (1992) Influence of ecosystematic factors on survival of escherichia-coli after large-scale release into lake water mesocosms. *Applied and Environmental Microbiology* 58 (7):2201-2210
84. Werlen C, Jaspers MCM, van der Meer JR (2004) Measurement of biologically available naphthalene in gas and aqueous phases by use of a pseudomonas putida biosensor. *Applied and Environmental Microbiology* 70 (1):43-51. doi:10.1128/aem.70.1.43-51.2004
85. Tauriainen S, Karp M, Chang W, Virta M (1998) Luminescent bacterial sensor for cadmium and lead. *Biosensors & Bioelectronics* 13 (9):931-938

